

HDS-5885TVI-IRD



Key Features

- 2 Megapixel high-performance CMOS
- Turbo HD output, up to 1080P resolution
- Fixed lens
- True Day/Night, Smart IR
- Up to 20m IR distance
- OSD menu controlled via UTC

Specification

Model	HDS-5885TVI-IRD
Parameter	Turbo HD1080p IR Dome Camera
Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Signal System	PAL/NTSC
Effective Pixels	1930(H)*1088(V)
Min. Illumination	0.1 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	3.6mm (6mm optional)
	Angle of View: 90°(3.6mm), 55.4°(6mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 350°, Tilt: 0 - 70°
Day & Night	ICR

Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 turbo HD output
CVBS Output	1Vp-p Composite Output(75Ω/BNC)
S/N Ratio	More than 52dB
Menu	
Camera ID	On/off (0-255)
AGC	Support
D/N Mode	Color/BW/Auto/EXT
White Balance	Auto/User/Push/8000K/6000K/4200K/3000K
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/Off
Language	English/Chinese
Functions	Digital noise reduction, Mirror
General	
Working Temperature/Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12V DC
Power Consumption	Max. 2.5W
IR Range	Up to 20m
Communication	Up the coax Protocol: Coaxitron
Dimension	Φ 98 x 65.4 mm (φ 3.86" x 2.57")
Weight	130 g (0.29 lb)

Dimension

