



1.3MP IR Mini Bullet Camera



Key features

- 1.3 megapixel high resolution
- HD video output
- Low illumination
- 3D DNR & DWDR & BLC
- IP66 rating
- IR range: up to 30m
- True day / night

Dimensions



Specifications

HDS-2012IRP	
Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR 0.028 lux @F2.0, AGC ON, 0 lux with IR
Shutter time	1/25s ~ 1/100,000s
Lens	6mm @F2.0 (4mm, 12mm optional) Angle of view: 45.3°
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Compression Standard	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Image	
Max. Image Resolution	1280 × 960
Frame rate	50Hz: 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps (1280 × 960), 30fps (1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
Network	
Network storage	NAS (iSCSI optional)
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Interface	
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
General	
Operating conditions	-25 °C ~ 60 °C (-13°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	max. 5W
Weather proof rating	IP66
IR range	Up to 30m
Dimension	60.4 x 76.5 x 138.1mm
Weight	300g

* Product picture and technical specs subject to change without previous notice.
For further information, please contact our local sales team.